



**BRITISH MANUFACTURING
EXCELLENCE SINCE 1962**



INTRODUCING GENERATION 2 WESSEX AR TRAILED FINISHING MOWERS

BUILDING ON 30 YEARS OF ATV INNOVATION, WE HAVE RE-ENGINEERED THE WESSEX AR FINISHING MOWER TO CREATE THE MOST VERSATILE FINISHING MOWER ON THE MARKET.



**IMAGE SHOWN:
IN SIDE-WHEEL CONFIGURATION**



**IMAGE SHOWN:
3 ROTORS WITH
OVERLAPPING BAFFLES**



**IMAGE SHOWN:
IN REAR-WHEEL
CONFIGURATION**



THE VERSATILITY OF GENERATION 2 WESSEX AR FINISHING MOWERS MAKES THEM THE FIRST CHOICE FOR MAINTAINING REGULARLY MOWN GRASS AREAS SUCH AS PRIVATE ESTATES, LAWNS AND PASTURES, ETC.

THEY ARE DESIGNED WITH THREE ROTORS WITH OVERLAPPING BAFFLES TO ENSURE EVEN GRASS DISTRIBUTION AND THE FINEST CUT QUALITY.

Market-leading SwingLock Axle system enables you to easily convert your **AR** mower from side wheels into a rear-wheel configuration in less than two minutes, and with zero tools or extra parts required! Perfect for mowing close to a fence.

Available in 1.2m and 1.5m with a choice of pull or electric start and complete with a 12.5hp (electric start) or 13.5hp (recoil start) powerful Briggs & Stratton engine, the Wessex **AR** finishing mower will complement any ATV, UTV or 4x4 and leave a superb finish in the process.

FEATURES AND BENEFITS

- ✓ **SWINGLOCK AXLE SYSTEM** (patent pending) – **MARKET-LEADING INNOVATION!** – Easily convert your AR Rotary Mower from side wheels into a rear-wheel configuration in less than two minutes, and with zero tools or extra parts required!
- ✓ **THREE ROTORS WITH OVERLAPPING BAFFLES** – Ensures even grass distribution and the finest cut quality.
- ✓ **SWIVELLING BALL HITCH** – Satisfies Health and Safety recommendations
- ✓ **TURN BUCKLE ON THE DRAWBAR** – Levels the machine for an even cut
- ✓ **DRAWBAR CAN BE OFFSET TO EITHER SIDE** – Cut outside of the ATV wheels
- ✓ **THROTTLE LEVER WITH KILL SWITCH** – Clips onto ATV rack for user convenience and safety
- ✓ **HEAVY DUTY BLADES WITH UPTURN ON TRAILING EDGE** – Durability and strong suction effect
- ✓ **18 X 8.5-8 TYRES** – Ideal for fine turf applications
- ✓ **POWERFUL BRIGGS & STRATTON ENGINE (B&S)** – With a choice of recoil or electric start
- ✓ **CENTRIFUGAL CLUTCH** – Allows the blades to be engaged or disengaged from the seat
- ✓ **SIMPLE BELT ADJUSTMENT** – Both belts are tensioned simultaneously by one simple sliding action of the engine

FROM SIDE TO REAR WHEELS IN LESS THAN 2 MINUTES!

Step 1

LEVEL MOWER



Step 2

REMOVE HAND WHEEL & BOLT



Step 3

SWING WHEELS TO REAR



Step 4

REFIT HAND WHEEL & BOLT



Step 5

RE-LEVEL MOWER



SPECIFICATIONS

	AR-120-R	AR-120-E	AR-150-R	AR-150-E
Cutting width	1.2m G2	1.2m G2	1.5m G2	1.5m G2
Overall width/side wheels	1.8m	1.8m	2.1m	2.1m
Cutting height range	25-200mm	25-200mm	25-200mm	25-200mm
Weight	200kg	200kg	235kg	235kg
Engine	12.5 HP	13.5 HP	12.5 HP	13.5 HP
Start	Recoil	Electric	Recoil	Electric

TRY IT FOR YOURSELF! CALL US TO BOOK YOUR FREE DEMO TODAY!

Call: 01264 345878 www.wessexintl.com

Follow us on: